


SMD Power Inductor 0618CDMCC/DS




Halogen Free




Description

- Metal compound molding type construction.
- Magnetically shielded.
- Low audible core noise.
- Suitable for large current.
- L × W × H: 7.3 × 6.8 × 1.8mm Max.
- Product weight: 0.45g (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

Dimension - [mm]



Land pattern and Schematics - [mm]



Environmental Data

- Operating temperature range: -55°C ~ +125°C (including coil's self temperature rise)
- Storage temperature range: -55°C ~ +125°C
- Solder reflow temperature: 260 °C peak.

Packaging

- Carrier tape and reel packaging.

Applications

- Ideally used in notebook, ultrabook, tablet PC, LCD display, Server application.
- High current, POL converters.
- Low profile, high current power supplies.
- Battery powered devices.
- DC/DC converters in distributed power systems.

SMD Power Inductor 0618CDMCC/DS



Electrical Characteristics

Part No.	Stamp	Inductance [Within] (μ H) ※1	D.C.R (m Ω) Max.(Typ.) at 25°C	Saturation Current (A) Max.(Typ.) (at 25°C) ※2	Temperature rise current (A) (Typ.) ※3
0618CDMCCDS-R68MC	R68	0.68 \pm 20%	12.0(10.0)	14.4(17.0)	9.8
0618CDMCCDS-1R0MC	1R0	1.0 \pm 20%	16.0(13.0)	12.1(14.3)	8.3
0618CDMCCDS-1R5MC	1R5	1.5 \pm 20%	26.0(20.0)	10.3(12.0)	7.0
0618CDMCCDS-2R2MC	2R2	2.2 \pm 20%	35.0(28.0)	9.2(10.8)	6.0
0618CDMCCDS-3R3MC	3R3	3.3 \pm 20%	50.0(43.0)	6.8(8.0)	4.7
0618CDMCCDS-4R7MC	4R7	4.7 \pm 20%	62.0(56.0)	5.3(6.3)	4.0
0618CDMCCDS-6R8MC	6R8	6.8 \pm 20%	110.0(101.0)	4.3(5.0)	3.0

※1 Measuring frequency Inductance at 100kHz ,1.0V

※2 Saturation current: The value of DC current when the inductance is over 70% of its initial value. (at 25°C)








※3 Temperature rise current: The actual value of DC current when temperature of coil rise is
 $\Delta T=40^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$)

SMD Power Inductor 0618CDMCC/DS



Saturation Current & Temperature Rise Graph



— L (20°C) — ΔT



SMD Power Inductor 0618CDMCC/DS



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Oberzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com