

Brand new 0150 series terminal block is designed for the industry of motion controller with the following characteristics.

- 🔈 1.Innovative smart clip helps to plug and unplug quickly and easily and provides reliable connection.
- 2.Rated voltage 300V/600V; rated current 16A/20A; pitch: 5.08 and 6.35mm
- 3.Innovative PID terminal block with integrated structure to make the wiring reliable and fast.
- 4.0150 series provides wide range of conductor cross section—AWG 24~12.
- 5.0150-20/30 plugs are space-saving with ultra-mini housing design of height 13.80mm
- 6.The product can be applied in different fields, such as motion controller or servo driver.




















6.35X(P-1)+8.00	26.70
6.35(P-1)   Red   6.55(P-1)   Red   6.55(P-1)	265

Pitch:5.08mm

Approval Page 1	us		
Technical Data	UL	IEC	
Rated voltage	300V	500V	
Rated current	16A	20A	
Conductor cross-section, solid (AWG/mm²)	24~12	0.2~4	
Conductor cross-section, flexible (AWG/mm²)	24~12	0.2~4	
Rated impulse voltage		4KV	
Torque(N-m)			
Screw			
Wire strip length	th 11mm		
Pole C	Cat.No.		
02 01	0150-2002		
:	:		
:	:		
16 01	0150-2016		

Pitch:6.35mm

Approval control contr			
Technical Data	UL	IEC	
Rated voltage	600V	800V	
Rated current	20A	24A	
Conductor cross-section, solid (AWG/mm²)	24~12	0.2~4	
Conductor cross-section, flexible (AWG/mm²)	24~12	0.2~4	
Rated impulse voltage		6KV	
Torque(N-m)			
Screw			
Wire strip length	11r	nm	
Pole Ca	Cat.No.		
02 015	0150-3002		
:	:		
:	:		
12 015	0150-3012		

Pitch:5.08mm

Approval	<b>7</b> L''s			
Technical Data	UL	IEC		
Rated voltage	300V	500V		
Rated current	16A	20A		
Conductor cross-section, solid (AWG/mm²)				
Conductor cross-section, flexible (AWG/mm²)				
Rated impulse voltage		4KV		
Torque(N-m)				
Screw				
Wire strip length				
Pole	Cat.No.			
02	0150-2602			
:	:			
:	:			
16	0150-2616			

Pitch:6.35mm

1 11011.0.00111111			
Approval	us		
Technical Data	UL	IEC	
Rated voltage	600V	800V	
Rated current	20A	24A	
Conductor cross-section, solid (AWG/mm²)			
Conductor cross-section, flexible (AWG/mm²)			
Rated impulse voltage		6KV	
Torque(N-m)			
Screw			
Wire strip length			
Pole	Cat.No.		
02 0	0150-3602		
:	:		
:	:		
12 0	0150-3612		

