

DC common mode choke coil

WCNFC322525L/DS



Features


- Special very low profile and small size SMD design.
- Wound Chip constructure with standard 0805 to 1812 size.
- Best EMI suppression effect but least impact to data signal wave form.
- Very high Self-resonance frequency enables high cut-off frequency.
- Excellent Solderability.
- L x W x H: 3.4x2.7x2.5mm Max.
- Moisture sensitivity level: MSL.1.
- RoHs & Halogen free compliance
- Operation temperature range: -40°C ~ 125 °C(Including coil's self heat)
- Storage temperature range: -40°C ~ 125 °C



Applications

- For common mode noise suppression in high-speed differential signal lines: USB 2.0, IEEE1394, LVDS, etc..
- High Speed differential signal lines for HDMI, DVI, etc..
- Audio lines.
- For USB 3.x application.
- Best for NB, DSC, mobile device design.
- Multimedia system and Ethernet(100BASE-T1).
- Common mode noise filter for power line.
- For LAN module application.

Dimensions (mm)




Note : This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.


DC common mode choke coil WCNFC322525L/DS



Land patterns (mm)



Terminal Connection



Electrical specifications

Part No.	Inductance (μ H) [Within] 1-2 (3-4)	Common mode Impedance (Ω) Min.(Typ.) 1-2 (3-4)	D.C.R (m Ω) Max. (Typ.) (1-2)OR (3-4)	Insulation resistance (M Ω) Min. (1-2)-(3-4)	Rated Voltage (Vdc) Max.	Temperature rise current (mA) ※1 Max. (1-2) OR (3-4)
	100kHz,0.1V	10MHz,0.5V	at 25°C	DC100V,60S		
WCNFC322525LDS-110	11+50%/-30%	300(550)	169(135)	10	50	810
WCNFC322525LDS-220	22+50%/-30%	500(1100)	474(379)	10	50	510
WCNFC322525LDS-510	51+50%/-30%	1000(2600)	598(478)	10	50	510
WCNFC322525LDS-101	100+50%/-30%	2200(5100)	1654(1323)	10	50	300

※1 Temperature rise current: The actual value of DC current when temperature of coil rise is $\Delta T=40^{\circ}\text{C}$ ($T_a=25^{\circ}\text{C}$)

(Test board condition:FR4,Copper=70 μ m,four-layer PWB t=1.6mm)


Note : This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.

DC common mode choke coil WCNFC322525L/DS




Common mode Impedance Characteristics

Impedance vs. frequency Common mode



Impedance vs. frequency Differential mode



For sales office information, please [click here](#) to visit our website.

Note : This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.