

SocketModem Feature Matrix

Models	Approvals			Input		Interface		Maximum Data Rate					FAX Capability					Features												
	US/Canada	US/Canada/Europe	Global w/ build option exceptions	Global	3.3 Volt	5 Volt	Serial	Parallel	V.22bis/2400 Baud	V.32bis/14.4K	V.34/33.6K	V.90/56K	V.92/56K	V.29/N.27/N.21 FAX	V.17 FAX	V.34 FAX	FAX Class 1	FAX Class 1.0	FAX Class 2	FAX Class 2.0	FAX Class 2.1	Caller ID	Leased Line	Fast/Quick connect	Voice (no SPK & MIC I/O)	Parallel phone detect/line detect	Temp Range -40 to +85 C°	3KV DAA isolation		
SocketModems (Regional)																														
SF224ATF/H0D5	X					X	X	X						X			X													
SF224ATF/H1D5	X					X	X	X						X			X													
SC144H0		X				X	X		X					X	X		X	X	X			X	X	X	X	X				
SC144H1		X				X	X		X					X	X		X	X	X			X	X	X	X	X				
SC144H1-L		X			X		X		X					X	X		X	X	X			X	X	X	X	X				
SC336H0		X				X		X			X			X	X		X	X	X			X	X	X	X	X				
SC336H1		X				X	X				X			X	X		X	X	X			X	X	X	X	X				
SC336H1-L		X			X		X				X			X	X		X	X	X			X	X	X	X	X				
SC56H0		X				X		X				X		X	X		X	X	X			X	X	X	X	X				
SC56H1		X				X	X					X		X	X		X	X	X			X	X	X	X	X				
SC56H1-L		X			X		X					X		X	X		X	X	X			X	X	X	X	X				
SocketModems (Global)																														
MT3400SMI				X	X		X			X												X	X	X	X					
MT3400SMI-P				X	X		X			X												X	X	X	X					
MT5600SMI				X	X		X				X											X	X	X	X					
MT5600SMI-P				X	X		X				X											X	X	X	X					
MT3334SMI (ENI or AUNZ)			X			X	X			X				X	X		X	X						X	X					
MT5634SMI (ENI or AUNZ)			X			X	X				X			X	X		X	X					X	X	X					
MT5634SMI-P (ENI or AUNZ)			X			X		X			X			X	X		X	X					X	X	X					
MT5634SMI-ITP (ENI or AUNZ)			X		X		X				X			X	X		X	X					X	X	X		X			
MT5634SMI-P-ITP (ENI or AUNZ)			X		X		X				X			X	X		X	X					X	X	X		X			
MT5634SMI-HV (ENI or AUNZ)			X			X	X				X			X	X		X	X					X	X	X				X	
MT5634SMI-P-HV (ENI or AUNZ)			X			X		X			X			X	X		X	X					X	X	X				X	
MT5634SMI-V92				X		X	X					X		X	X	X	X	X	X	X	X		X	X	X					
MT5634SMI-P-V92				X		X		X				X		X	X	X	X	X	X	X	X		X	X	X					

