

# Migrating from AT89S8252/S53 to AT89S8253



## New Features

- 64-byte User Signature Array
- Enhanced UART with Frame Detection and Automatic Address Recognition
- Enhanced SPI (Double Write/Read Buffered) Serial Interface
- Page Mode in both Parallel/Serial Programming Modes (Code/Data Memories)
- Four-level Enhanced Interrupt Controller
- Programmable and Fuseable x2 Clock Option
- Internal Power-on Reset
- 42-pin PDIP Package Option for Reduced EMI Emission
- EEPROM Page Write Access during CPU Execution

## Introduction

The purpose of this application note is to help users convert existing designs from AT89S8252/S53 to AT89S8253. The given information will also help migration from AT89LS8252/LS53 to AT89S8253. This application note describes AT89S8253 memory sizes, features, and SFR mapping. More detailed information can be found in the AT89S8253 datasheet.

## Memory Sizes

The following table shows a comparison of the individual memories.

Memory	AT89S8252	AT89S53	AT89S8253
Flash	8K Bytes	12K Bytes	12K Bytes
RAM	256 Bytes	256 Bytes	256 Bytes
EEPROM	2K Bytes	N/A	2K Bytes

## 64-byte User Signature Array

Sixty-four bytes are accessible to the user to program their own desired data. Bytes can be either programmed by parallel or serial mode.

## Flash Microcontrollers

## Application Note





### **Enhanced UART with Frame Error Detection and Automatic Address Recognition**

When used for frame error detection, the UART looks for missing stop bits in the communication. A missing bit will set the FE bit in the SCON Register. Automatic Address Recognition allows the UART to recognize certain addresses in the serial bit stream by using hardware to make the comparison.

### **Enhanced SPI (Double Write/Read Buffered) Serial Interface**

The enhanced SPI mode allows the write buffer to hold the next byte to be transmitted. As long as the CPU can keep the write buffer full, multiple bytes may be transferred with minimal latency between bytes.

### **Page Mode in both Parallel/Serial Programming Modes (Code/Data Memories)**

Program and data memories can be programmed in page mode (1 code page = 64 bytes; data page = 32 bytes).

Page mode is available in both the parallel and serial programming modes.

### **Four-level Enhanced Interrupt Controller**

Each interrupt source can be individually programmed to one of four priority levels by setting or clearing a bit in the Interrupt Priority (IP) register and in the Interrupt Priority High (IPH) register.

The Interrupt Priority High register shows the bit values and priority levels associated with each combination.

### **Programmable and Fuseable x2 Clock Option**

The x2 clock option allows the microcontroller to execute one machine cycle in 6 clock periods instead of 12 clock periods. This can be set either through hardware or software.

### **Internal Power-On Reset**

A 1 ms internal reset signal will be generated after power-on, eliminating the need for any external Power-on reset circuitry.

### **42-pin PDIP Package Option for Reduced EMI Emission**

The 42-pin package has extra pins PWRVDD and PWRGND to reduce EMI Emission. PWRVDD must be connected to the application board supply voltage. PWRGND must be connected to the application board GND.

### **EEPROM Page Write during CPU Execution**

During CPU execution, EEPROM can be written one page (32 bytes) at a time. This way, 32 bytes will only require 4 ms of programming time instead of 128 ms required in single byte programming.

### **Operational $V_{CC}$ Voltage Range**

While the AT89S8252/S53 are offered in low-voltage versions as AT89LS8252/LS53, respectively, the AT89S8253 nomenclature encompasses both the regular (4.0V to 5.5V) and low-voltage (2.7V to 4.0V) operational  $V_{CC}$  voltage ranges. The ordering is designated by the appropriate operational frequency range. Please consult the Ordering Information table in the AT89S8253 device datasheet.

# Migrating from AT89S8252/S53 to AT89S8253

## SFRs Mapping

The highlighted SFR locations are new registers for the AT89S8253 device.

0F8H									0FFH
0F0H	B								0F7H
0E8H									0EFH
0E0H	ACC								0E7H
0D8H									0DFH
0D0H	PSW						SPCR		0D7H
0C8H	T2CON	T2MOD	RCAP2L	RCAP2H	TL2	TH2			0CFH
0C0H									0C7H
0B8H	IP	SADEN							0BFH
0B0H	P3							IPH	0B7H
0A8H	IE	SADDR	SPSR						0AFH
0A0H	P2						WDTRST	WDTCON	0A7H
98H	SCON	SBUF							9FH
90H	P1						EECON		97H
88H	TCON	TMOD	TL0	TL1	TH0	TH1	AUXR	CLKREG	8FH
80H	P0	SP	DP0L	DP0H	DP1L	DP1H	SPDR	PCON	87H

**Note:** 1. In the AT89S8253, the DP0L/H register pair always accesses DPTR0 and the DP1L/H pair always accesses DPTR1 regardless of the state of the DPS bit in SFR EECON. This is different than in the AT89S8252/AT89S53 devices, where the DPL/H switch between DPTR0 and DPTR1 is based on the state of the DPS bit. For further information on the dual data pointer usage, refer to the AT89S8253 datasheet and to the application note titled “AT89S8252 Primer” located in Atmel’s web site.



## Fuse Table

Fuse	AT89S8252	AT89S53	AT89S8253
SerialProg	Yes	Yes	Yes
x2 Clock	No	No	Yes
UserRowProg	No	No	Yes

## Programming Time (Byte Mode)

Part Number	Flash (Reset = High)	EEPROM (Reset = High)	EEPROM Reset = Low (CPU Execution)
AT89S8252	12 sec	2.7 sec	5.12 sec
AT89S53	16 sec	N/A	N/A
AT89S8253	N/A	N/A	N/A

## Programming Time (Page Mode)

Part Number	Flash (Reset = High)	EEPROM (Reset = High)	EEPROM Reset = Low (CPU Execution)
AT89S8252	N/A	N/A	N/A
AT89S53	N/A	N/A	N/A
AT89S8253	0.96 sec	0.32 sec	0.256 sec



## Atmel Corporation

2325 Orchard Parkway  
San Jose, CA 95131, USA  
Tel: 1(408) 441-0311  
Fax: 1(408) 487-2600

## Regional Headquarters

### Europe

Atmel Sarl  
Route des Arsenalux 41  
Case Postale 80  
CH-1705 Fribourg  
Switzerland  
Tel: (41) 26-426-5555  
Fax: (41) 26-426-5500

### Asia

Room 1219  
Chinachem Golden Plaza  
77 Mody Road Tsimshatsui  
East Kowloon  
Hong Kong  
Tel: (852) 2721-9778  
Fax: (852) 2722-1369

### Japan

9F, Tonetsu Shinkawa Bldg.  
1-24-8 Shinkawa  
Chuo-ku, Tokyo 104-0033  
Japan  
Tel: (81) 3-3523-3551  
Fax: (81) 3-3523-7581

## Atmel Operations

### Memory

2325 Orchard Parkway  
San Jose, CA 95131, USA  
Tel: 1(408) 441-0311  
Fax: 1(408) 436-4314

### Microcontrollers

2325 Orchard Parkway  
San Jose, CA 95131, USA  
Tel: 1(408) 441-0311  
Fax: 1(408) 436-4314

La Chantrerie  
BP 70602  
44306 Nantes Cedex 3, France  
Tel: (33) 2-40-18-18-18  
Fax: (33) 2-40-18-19-60

### ASIC/ASSP/Smart Cards

Zone Industrielle  
13106 Rousset Cedex, France  
Tel: (33) 4-42-53-60-00  
Fax: (33) 4-42-53-60-01

1150 East Cheyenne Mtn. Blvd.  
Colorado Springs, CO 80906, USA  
Tel: 1(719) 576-3300  
Fax: 1(719) 540-1759

Scottish Enterprise Technology Park  
Maxwell Building  
East Kilbride G75 0QR, Scotland  
Tel: (44) 1355-803-000  
Fax: (44) 1355-242-743

### RF/Automotive

Theresienstrasse 2  
Postfach 3535  
74025 Heilbronn, Germany  
Tel: (49) 71-31-67-0  
Fax: (49) 71-31-67-2340

1150 East Cheyenne Mtn. Blvd.  
Colorado Springs, CO 80906, USA  
Tel: 1(719) 576-3300  
Fax: 1(719) 540-1759

### Biometrics/Imaging/Hi-Rel MPU/ High Speed Converters/RF Datacom

Avenue de Rochepleine  
BP 123  
38521 Saint-Egreve Cedex, France  
Tel: (33) 4-76-58-30-00  
Fax: (33) 4-76-58-34-80

---

### Literature Requests

[www.atmel.com/literature](http://www.atmel.com/literature)

**Disclaimer:** Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

© Atmel Corporation 2004. All rights reserved. Atmel® and combinations thereof are the registered trademarks of Atmel Corporation or its subsidiaries. Other terms and product names may be the trademarks of others.



Printed on recycled paper.

3449A-MICRO-6/04