



AC/DC Medical Series	Model No.	Voltage (V)	Load (A)	Sense	V Adjust	Leakage Current (µA)	No Load Power (W)
<b>40 Watt (MWLT)</b> • 4.0 x 2.0 x 1.2 inches • 40 W convection-cooled • Class 1 & 2 options • IEC60601-1 (Ed.3) approved	LFMWLT40-1000	5.1	8.0	Yes	+/-10%	< 250	< 0.3
	LFMWLT40-1001	12	3.5	Yes	+/-10%	< 250	< 0.3
	LFMWLT40-1002	15	2.7	Yes	+/-10%	< 250	< 0.3
	LFMWLT40-1003	24	1.7	Yes	+/-10%	< 250	< 0.3
	LFMWLT40-1004	48	0.83	Yes	+/-10%	< 250	< 0.3
	LFMWLT40-3000	5.2, 12.5, -12.8	6.0, 2.0, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT40-3001	5.2, 24, -12.8	6.0, 1.0, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT40-3002	5.2, 14.6, -14.8	6.0, 1.5, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT40-3003	3.3, 5.2, -12.8	6.0, 3.0, 0.5	Yes	+/-10%	< 250	< 0.5



<b>60 Watt (MWLT)</b> • 4.0 x 2.0 x 1.2 inches • 60 W convection-cooled • Class 1 & 2 options • IEC60601-1 (Ed.3) approved	LFMWLT60-1000	5.1	10.0	Yes	+/-10%	< 250	< 0.3
	LFMWLT60-1001	12	5.4	Yes	+/-10%	< 250	< 0.3
	LFMWLT60-1002	15	4.33	Yes	+/-10%	< 250	< 0.3
	LFMWLT60-1003	24	2.7	Yes	+/-10%	< 250	< 0.3
	LFMWLT60-1004	48	1.35	Yes	+/-10%	< 250	< 0.3
	LFMWLT60-3000	5.2, 12.5, -12.8	8.0, 3.0, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT60-3001	5.2, 24, -12.8	8.0, 1.5, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT60-3002	5.2, 14.6, -14.8	8.0, 2.5, 0.5	Yes	+/-10%	< 250	< 0.5
	LFMWLT60-3003	3.3, 5.2, -12.8	8.0, 3.0, 0.5	Yes	+/-10%	< 250	< 0.5



<b>80 Watt (MWLT)</b> • 5.0 x 3.04 x 1.07 inches • 60 to 80 W convection-cooled • Class 1 product • IEC60601-1 (Ed.3) approved	LFMVL80-1000	5.1	12.0	No	Fixed	< 250	2.2
	LFMVL80-1001	12	6.8	No	Fixed	< 250	2.2
	LFMVL80-1002	15	5.5	No	Fixed	< 250	2.2
	LFMVL80-1003	24	3.4	No	Fixed	< 250	2.2
	LFMVL80-1004	48	1.7	No	Fixed	< 250	2.2
	LFMVL80-4000	5.1, 12.25, -5.1, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	< 250	2.2
	LFMVL80-4001	5.1, 24, 12.5, -12.5	10.0, 2.0, 0.8, 0.8	No	Fixed	< 250	2.2
	LFMVL80-4002	5.1, 15.9, -5.1, -15.9	10.0, 3.0, 0.8, 0.8	No	Fixed	< 250	2.2
	LFMVL80-4003	5.1, 12.25, 23.6, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	< 250	2.2
	LFMVL80-4004	3.3, 5.1, 12.5, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	< 250	2.2



<b>110 Watt (MWLT)</b> • 5.0 x 3.04 x 1.07 inches • 80 to 110 W fan-cooled • Class 1 product • IEC60601-1 (Ed.3) approved	LFMVL110-1300	5.1	18.0	No	Fixed	< 250	2.85
	LFMVL110-1301	12	9.2	No	Fixed	< 250	2.85
	LFMVL110-1302	15	7.3	No	Fixed	< 250	2.85
	LFMVL110-1303	24	4.6	No	Fixed	< 250	2.85
	LFMVL110-1304	48	2.3	No	Fixed	< 250	2.85
	LFMVL110-4300	5.1, 12.4, -5.1, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	< 250	2.85
	LFMVL110-4301	5.1, 23.5, 12.5, -12.5	15.0, 2.75, 1.1, 1.1	No	Fixed	< 250	2.85
	LFMVL110-4302	5.1, 16, -5.1, -16	15.0, 4.1, 1.1, 1.1	No	Fixed	< 250	2.85
	LFMVL110-4303	5.1, 12.4, 24, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	< 250	2.85
	LFMVL110-4304	3.3, 5.1, 12.5, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	< 250	2.85



<b>150 Watt (MWLT)</b> • 4.0 x 2.0 x 1.324 inches • 150 W fan-cooled • Class 1 & 2 options • IEC60601-1 (Ed.3) approved	LFMWLT150-1000	5	20.0*/16.0	No	+/-3%	< 250	1.2
	LFMWLT150-1001	12	12.5	No	+/-3%	< 250	1.2
	LFMWLT150-1002	15	10.0	No	+/-3%	< 250	1.2
	LFMWLT150-1003	24	6.25	No	+/-3%	< 250	1.2
	LFMWLT150-1004	48	3.13	No	+/-3%	< 250	1.2



<b>200 Watt (MWLT)</b> • 5.0 x 3.0 x 1.5 inches • 160 to 200 W fan-cooled • Class 1 & 2 options • IEC60601-1 (Ed.3) approved	LFMWLT200-1000	5	35.0*/26.0	Yes	+/-3%	< 250	0.8
	LFMWLT200-1001	12	16.67	Yes	+/-3%	< 250	0.8
	LFMWLT200-1002	15	13.33	Yes	+/-3%	< 250	0.8
	LFMWLT200-1003	24	8.33	Yes	+/-3%	< 250	0.8
	LFMWLT200-1004	48	4.17	Yes	+/-3%	< 250	0.8



<b>300 Watt (MWLT)</b> • 5.0 x 3.0 x 1.5 inches • 200 to 325 W fan-cooled • Class 1 & 2 options • IEC60601-1 (Ed.3) approved	LFMWLT300-1000-3	5	40.0	Yes	+/-3%	< 250	0.8
	LFMWLT300-1001-3	12	25.0	Yes	+/-3%	< 250	0.8
	LFMWLT300-1002-3	15	20.0	Yes	+/-3%	< 250	0.8
	LFMWLT300-1003-3	24	13.54	Yes	+/-3%	< 250	0.8
	LFMWLT300-1004-3	48	6.77	Yes	+/-3%	< 250	0.8
	LFMWLT300-1005-3	30	10.83	Yes	+/-3%	< 250	0.8



AC/DC Industrial Series	Model No.	Voltage (V)	Load (A)	Sense	V Adjust	Efficiency (%)	No Load Power (W)
<b>40 Watt (WLT)</b> • 4.0 x 2.0 x 1.2 inches • 40 W convection-cooled • Class 1 & 2 options • IEC60950-1 (Ed.2) approved	LFWLT40-1000	5.1	8.0	Yes	+/-10%	85	< 0.3
	LFWLT40-1001	12	3.5	Yes	+/-10%	85	< 0.3
	LFWLT40-1002	15	2.7	Yes	+/-10%	85	< 0.3
	LFWLT40-1003	24	1.7	Yes	+/-10%	85	< 0.3
	LFWLT40-1004	48	0.83	Yes	+/-10%	85	< 0.3
	LFWLT40-3000	5.2, 12.5, -12.8	6.0, 2.0, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT40-3001	5.2, 23.8, -12.8	6.0, 1.0, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT40-3002	5.2, 14.6, -14.8	6.0, 1.5, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT40-3003	3.3, 5.2, -12.8	6.0, 3.0, 0.5	Yes	+/-10%	75	< 0.5



<b>60 Watt (WLT)</b> • 4.0 x 2.0 x 1.2 inches • 60 W convection-cooled • Class 1 & 2 options • IEC60950-1 (Ed.2) approved	LFWLT60-1000	5.2	10.0	Yes	+/-10%	85	< 0.3
	LFWLT60-1001	12	5.4	Yes	+/-10%	85	< 0.3
	LFWLT60-1002	15	4.33	Yes	+/-10%	85	< 0.3
	LFWLT60-1003	24	2.7	Yes	+/-10%	85	< 0.3
	LFWLT60-1004	48	1.35	Yes	+/-10%	85	< 0.3
	LFWLT60-3000	5.2, 12.5, -12.5	8.0, 3.0, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT60-3001	5.2, 23.8, -12.5	8.0, 1.5, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT60-3002	5.2, 14.6, -16.2	8.0, 2.5, 0.5	Yes	+/-10%	82	< 0.5
	LFWLT60-3003	3.3, 5.2, -12.8	8.0, 3.0, 0.5	Yes	+/-10%	75	< 0.5



<b>80 Watt (WLT)</b> • 5.0 x 3.04 x 1.07 inches • 60 to 80 W convection-cooled • Class 1 product • IEC60950-1 (Ed.2) approved	LFVLT80-1000	5.1	12.0	No	Fixed	80	2.2
	LFVLT80-1001	12	6.8	No	Fixed	80	2.2
	LFVLT80-1002	15	5.5	No	Fixed	80	2.2
	LFVLT80-1003	24	3.4	No	Fixed	80	2.2
	LFVLT80-1008	36	2.2	No	Fixed	80	2.2
	LFVLT80-1004	48	1.7	No	Fixed	80	2.2
	LFVLT80-4000	5.1, 12.4, -5.1, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	85	2.2
	LFVLT80-4001	5.1, 23.5, 12.5, -12.5	10.0, 2.0, 0.8, 0.8	No	Fixed	85	2.2
	LFVLT80-4002	5.1, 16, -5.1, -16	10.0, 3.0, 0.8, 0.8	No	Fixed	85	2.2
	LFVLT80-4003	5.1, 12.4, 24, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	85	2.2
	LFVLT80-4004	3.3, 5.1, 12.5, -12.5	10.0, 3.0, 0.8, 0.8	No	Fixed	80	2.2



<b>100 Watt (WLT)</b> • 5.0 x 3.04 x 1.07 inches • 80 to 110 W fan-cooled • Class 1 product • IEC60950-1 (Ed.2) approved	LFVLT100-1001	12	7.5	No	Fixed	90	8.5
	LFVLT100-1002	15	6.67	No	Fixed	90	8.5
	LFVLT100-1003	24	4.2	No	Fixed	90	8.5
	LFVLT100-1004	48	2.1	No	Fixed	90	8.5
	LFVLT100-4000	5.1, 12.25, -5, -12	12.0, 4.0, 0.8, 0.8	No	Fixed	86	8.5
	LFVLT100-4001	5.1, 24.5, 12, -12	12.0, 2.0, 0.8, 0.8	No	Fixed	86	8.5
	LFVLT100-4002	5.1, 16, -4.8, -15.5	12.0, 3.0, 0.8, 0.8	No	Fixed	86	8.5
	LFVLT100-4003	5.1, 12, 24, -12	12.0, 4.0, 0.8, 0.8	No	Fixed	86	8.5



<b>110 Watt (WLT)</b> • 5.0 x 3.04 x 1.07 inches • 80 to 110 W fan-cooled • Class 1 product • IEC60950-1 (Ed.2) approved	LFVLT110-1300	5.1	18.0	No	Fixed	80	2.85
	LFVLT110-1301	12	9.2	No	Fixed	80	2.85
	LFVLT110-1302	15	7.3	No	Fixed	80	2.85
	LFVLT110-1303	24	4.6	No	Fixed	80	2.85
	LFVLT110-1304	48	2.3	No	Fixed	80	2.85
	LFVLT110-4300	5.1, 12.4, -5.1, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	82	2.85
	LFVLT110-4301	5.1, 23.5, 12.5, -12.5	15.0, 2.75, 1.1, 1.1	No	Fixed	82	2.85
	LFVLT110-4302	5.1, 16, -5.1, -16	15.0, 4.1, 1.1, 1.1	No	Fixed	82	2.85
	LFVLT110-4303	5.1, 12.4, 24, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	82	2.85
	LFVLT110-4304	3.3, 5.1, 12.5, -12.5	15.0, 4.1, 1.1, 1.1	No	Fixed	80	2.85



<b>130 Watt (WLT)</b> • 5.0 x 3.04 x 1.07 inches • 80 to 130 W fan-cooled • Class 1 product • IEC60950-1 (Ed.2) approved	LFVLT130-1106	3.3	32.0	Yes	Fixed	77	3.85
	LFVLT130-1100	5.1	25.5	Yes	Fixed	77	3.85
	LFVLT130-1101	12	10.8	Yes	Fixed	86	3.85
	LFVLT130-1102	15	8.7	Yes	Fixed	86	3.85
	LFVLT130-1103	24	5.4	Yes	Fixed	86	3.85
	LFVLT130-1104	48	2.7	Yes	Fixed	86	3.85
	LFVLT130-4100	5.1, 3.3, 12.7, -12.4	14.0, 16.0, 1.5, 1.5	Yes	Fixed	81	3.85
	LFVLT130-4101	5.1, 3.3, 24, -12.0	14.0, 16.0, 1.5, 1.5	Yes	Fixed	81	3.85
	LFVLT130-4102	5.1, 3.3, 16.3, -16.3	14.0, 16.0, 1.5, 1.5	Yes	Fixed	81	3.85



AC/DC Industrial Series	Model No.	Voltage (V)	Load (A)	Sense	V Adjust	Efficiency (%)	No Load Power (W)
<b>150 Watt (VLT)</b> • 5.0 x 3.04 x 1.07 inches • 80 to 150 W fan-cooled • Class 1 product • IEC60950-1 (Ed.2) approved	LFVLT150-1106	3.3	36.0	Yes	Fixed	85	3.85
	LFVLT150-1100	5.1	29.4	Yes	Fixed	85	3.85
	LFVLT150-1101	12	12.5	Yes</			