



DIN-RAIL MOUNT POWER SUPPLIES Full Function Series

KH30/60/90/120/240/480







5-Year Warranty

L'ANUS & CE ROHS





Safety agency approvals

UL60950-1, C-UL (CSA60950-1), UL508 and ANSI/ISA12. 12.01 are approved. GL safety standard is also approved (120W and 240W only).



Remote control terminal included as standard. Power line ON / OFF control is simple.



Among the world's highest power density

We have increased power density by reducing internal loss to be among the world's highest. Make your control panel narrower, smaller and lighter.



 $5.4\,\mathrm{W/in^3}$

Peak power (120W, 240W and 480W only)

The power supply is equipped with peak power of 1.5 times rated. This allows start up of machines with a large inrush current.

Two choices of interface

Two types of interface are available, depending on where you install. Captured screw feature simplifies wiring work.

《European type》《Block type》





2WAY

Superior convection

By optimizing component distribution, we have achieved the operating temperature range of -25°C ~ +70°C for KH120F-480F and -20°C ~ +70°C for KH30F-90F. It is ideal for use in an enclosed space such as acontrol

(Product Outline)

Model		KH30F	KH60F	KH90F	KH120F	KH240F	KH480F
Maximum power output [W]		31.2	60	91.2	120	240	480
Input voltage [V]		AC85~264 1φ			AC85~264 1¢ or DC120~370		
Output	Voltage [V]	24	24	24	24	24	24
	Current [A]	1.3	2.5	3.8	5	10	20
	Peak current [A]	- H - H - H	_	_	7.5	15	30
Structure	Case size (W×H×D)	22.5×75×90mm	32×90×90mm	50×90×90mm	37×124×117mm	50×124×117mm	70×127×117mm
		0.89×2.95×3.54 inches	1.26×3.54×3.54 inches	1.97×3.54×3.54 inches	1.46×4.88×4.61 inches	1.97×4.88×4.61 inches	2.76×4.88×4.61inches
	Weight	150g max	270g max	405g max	700g max	900g max	1200g max

COSEL CO., LTD.

www.cosel.co.jp/en/

Asia/China: sales@coselasia.com North America: sales@coselusa.com Europe: sales@coseleurope.eu